

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: **FUSOR® 132, 133 PLASTIC REPAIR ADH PT A**
Product Use/Class: **URETHANE ADHESIVE, PART 1 OF 2**

LORD Corporation
111 LORD Drive
Cary, NC 27511-7923 USA

Telephone: 814 868-3180
Non-Transportation Emergency: 814 763-2345
Chemtrec 24 Hr Transportation Emergency No.
800 424-9300 (Outside Continental U.S. 703 527-3887)

Connell Bros. Co. Australasia Pty Ltd.
Unit 3 / 257 Leitchs Road
Brendale QLD 4500 Australia
ABN 53 079 159 327
Telephone: 07 3552 9200
Australia Wide - 24 Hr Emergency Number
1800-033-111

EFFECTIVE DATE: 03/10/2023

2. HAZARDS IDENTIFICATION**GHS CLASSIFICATION:**

Acute toxicity Inhalation - Dust and Mist Category 4 - 18.5% of the mixture consists of ingredient(s) of unknown toxicity.
Acute toxicity Inhalation - Vapour Category 5 - 18.5% of the mixture consists of ingredient(s) of unknown toxicity.
Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2A
Skin sensitization Category 1
Respiratory sensitization Category 1
Specific target organ systemic toxicity (single exposure) Category 1 Respiratory system
Specific target organ systemic toxicity (single exposure) Category 3
Specific target organ systemic toxicity (repeated exposure) Category 1 Respiratory system

GHS LABEL ELEMENTS:**Symbol(s)****Signal Word**

DANGER

Hazard statements

Harmful if inhaled.
Causes skin irritation.

Causes serious eye irritation.
May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Causes damage to organs.(Respiratory system)
May cause respiratory irritation.
Causes damage to organs through prolonged or repeated exposure.(Respiratory system)

Precautionary statements

Prevention

Wear protective gloves, eye protection, face protection.
In case of inadequate ventilation wear respiratory protection.
Do not breathe dust, fume, mist, vapors, spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.

Response

Call a POISON CENTER or doctor, physician if you feel unwell.
IF exposed: Call a POISON CENTER or doctor, physician.
Specific treatment (see supplemental first aid instructions on this label).
IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
If experiencing respiratory symptoms: Call a POISON CENTER or doctor, physician.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice, attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Take off contaminated clothing and wash before reuse.

Storage

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

Disposal:

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

Other hazards:

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

Acute: Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. May cause lung damage. Animal tests have indicated that respiratory sensitization can result from skin contact with certain isocyanates. May be harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

Chronic: May cause long-term lung damage. IARC has designated carbon black as Group 2B - inadequate evidence for carcinogenicity in humans, but sufficient evidence in experimental animals. In 2006 IARC reaffirmed its 1995 finding that there is "inadequate evidence" from human health studies to assess whether carbon black causes cancer in humans. Further, epidemiological evidence from well-conducted investigations has shown no causative link between carbon black exposure and the risk of malignant or non-malignant respiratory disease in humans.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients above the threshold concentration

Chemical Name	CAS Number	Range
---------------	------------	-------

4,4'-Diphenylmethane diisocyanate	101-68-8	15 - 20 %
Aromatic polyisocyanate	PROPRIETARY	10 - 15 %
Diphenylmethane diisocyanate	26447-40-5	5 - 10 %
Carbon black	1333-86-4	1 - 5 %

4. FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention. Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

FIRST AID - SKIN CONTACT: Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

FIRST AID - INHALATION: Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Dry chemical, Foam, Water fog

UNSUITABLE EXTINGUISHING MEDIA: Not determined for this product.

SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL: Keep container tightly closed. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: Wear full firefighting protective clothing, including self contained breathing apparatus. If water is used, fog nozzles are preferable.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Avoid breathing vapors. Use self-contained breathing equipment. Avoid contact.

ENVIRONMENTAL PRECAUTIONS: Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of this safety data sheet. Scoop spilled material into an appropriate container for proper disposal. (If necessary, use inert absorbent material to aid in containing the spill).

7. HANDLING AND STORAGE

HANDLING: Keep closure tight and container upright to prevent leakage. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation.

STORAGE: Store only in well-ventilated areas. Keep container closed when not in use.

INCOMPATIBILITY: Strong bases and oxidizers.; Amines, acids, water, hydroxyl, or active hydrogen compounds.; This product will react with any materials containing active hydrogens, such as water, alcohol, ammonia, amines, alkalis and acids. The reaction with water is accelerated at temperatures higher than 122F (50C) and in the presence of alkalis, tertiary amines, and metal compounds. Some reactions can be violent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

COMPONENT EXPOSURE LIMIT

4,4'-Diphenylmethane diisocyanate	101-68-8	Australia STEL: 0.07 mg/m3 Australia TWA: 0.02 mg/m3 ACGIH-TWA: 0.005 ppm
Aromatic polyisocyanate	PROPRIETARY	Australia STEL: 0.07 mg/m3 Australia TWA: 0.02 mg/m3
Diphenylmethane diisocyanate	26447-40-5	Not established
Carbon black	1333-86-4	Australia TWA: 3 mg/m3

ENGINEERING CONTROLS: Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits.

PERSONAL PROTECTION MEASURES/EQUIPMENT:

Respiratory protection: This product contains isocyanates which have poor odor warning properties. If occupational exposure limits are exceeded, a NIOSH approved supplied-air respirator is required. For respirator use observe OSHA regulations (29CFR 1910.134) or use in accordance with applicable laws and regulations of your country or particular locality. This product contains isocyanates which have poor odor warning properties. If occupational exposure limits are exceeded, a NIOSH approved supplied-air respirator is required. For respirator use observe OSHA regulations (29CFR 1910.134) or use in accordance with applicable laws and regulations of your country or particular locality.

Skin protection: Use neoprene, nitrile, or rubber gloves to prevent skin contact. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Eye protection: Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

Other protective equipment: Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse. Use long-sleeved shirt to minimize skin exposure.

Hygienic practices: Wash hands before eating, smoking, or using toilet facility. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

Odor: Odorless

Vapor Pressure: N.D.

Appearance:	Black	Vapor density:	Heavier than Air
Physical state:	Paste	Lower explosion limit:	N.A.
Flash point:	≥ 201 °F, 93 °C	Upper explosive limit:	N.A.
	Setaflash Closed Cup		
Boiling range:	N.A.	Evaporation rate:	Slower than n-butyl- acetate
Autoignition temperature:	N.D.	Density:	1.53 g/cm ³
Decomposition temperature:	N.D.	Viscosity, dynamic:	≥ 40 mPa.s @ 25 °C
Odor threshold:	N.D.	Viscosity, kinematic:	≥ 26 mm ² /s @ 25 °C
Solubility in H₂O:	Insoluble	Volatile by weight:	0.00 %
pH:	N.A.	Volatile by volume:	0.00 %
Freeze point:	N.D.	VOC Calculated:	0 lb/gal, 0 g/10 g/l
Coefficient of water/oil distribution:	N.D.		

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Hazardous polymerisation will not occur under normal conditions.

STABILITY: Product is stable under normal storage conditions.

CONDITIONS TO AVOID: Moisture; High temperatures.; Unwanted, rapid and potentially hazardous polymerization may occur upon reaction with water at high temperatures or in the presence of alkalies, tertiary amines, and metal compounds.

INCOMPATIBILITY: Strong bases and oxidizers.; Amines, acids, water, hydroxyl, or active hydrogen compounds.; This product will react with any materials containing active hydrogens, such as water, alcohol, ammonia, amines, alkalies and acids. The reaction with water is accelerated at temperatures higher than 122F (50C) and in the presence of alkalies, tertiary amines, and metal compounds. Some reactions can be violent.

HAZARDOUS DECOMPOSITION PRODUCTS: Does not decompose when used and stored as recommended., Monomeric isocyanate, traces of hydrogen cyanide, nitrogen dioxide., Carbon monoxide, carbon dioxide.

11. TOXICOLOGICAL INFORMATION

EXPOSURE PATH: Refer to section 2 of this SDS.

SYMPTOMS: Refer to section 2 of this SDS.

CHRONIC EFFECTS: Refer to section 2 of this SDS.

TOXICITY MEASURES:

Acute toxicity Inhalation - Dust and Mist: Category 4 - Harmful if inhaled.

Components contributing to classification: 4,4'-Diphenylmethane diisocyanate. Aromatic polyisocyanate. Diphenylmethane diisocyanate.

Acute toxicity Inhalation - Vapour: Category 5

Components contributing to classification: 4,4'-Diphenylmethane diisocyanate. Aromatic polyisocyanate. Diphenylmethane diisocyanate.

Chemical Name	LD50/LC50
4,4'-Diphenylmethane diisocyanate	Oral LD50: Rat 31,600 mg/kg Dermal LD50: rabbit > 5,000 mg/kg GHS LC50 (vapour): Acute toxicity point estimate 11 mg/l / 4 hGHS LC50

	(dust and mist): Acute toxicity point estimate 1.5 mg/l /4 h
Aromatic polyisocyanate	Oral LD50: Rat 49 g/kg Dermal LD50: Rabbit > 9,400 mg/kg Dermal LD50: Rabbit > 9.4 g/kg GHS LC50 (vapour): Acute toxicity point estimate 11 mg/l GHS LC50 (dust and mist): Acute toxicity point estimate 1.5 mg/l
Diphenylmethane diisocyanate	Oral LD50: Rat > 10,000 mg/kg Dermal LD50: Rabbit > 10,000 mg/kg GHS LC50 (vapour): Acute toxicity point estimate 11.0 mg/l GHS LC50 (dust and mist): Acute toxicity point estimate 1.5 mg/l
Carbon black	Oral LD50: Rat > 15,400 mg/kg Dermal LD50: Rabbit > 3 g/kg GHS LC50 (vapour): Acute toxicity point estimate 55 mg/l

Skin corrosion/irritation: Category 2 - Causes skin irritation.

Components contributing to classification: 4,4'-Diphenylmethane diisocyanate. Aromatic polyisocyanate. Diphenylmethane diisocyanate.

Serious eye damage/eye irritation: Category 2A - Causes serious eye irritation.

Components contributing to classification: 4,4'-Diphenylmethane diisocyanate. Aromatic polyisocyanate. Diphenylmethane diisocyanate.

Skin sensitization: Category 1 - May cause an allergic skin reaction.

Components contributing to classification: 4,4'-Diphenylmethane diisocyanate. Aromatic polyisocyanate. Diphenylmethane diisocyanate.

Respiratory sensitization: Category 1 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Components contributing to classification: 4,4'-Diphenylmethane diisocyanate. Aromatic polyisocyanate. Diphenylmethane diisocyanate.

Germ cell mutagenicity: No classification proposed

Carcinogenicity:

Reproductive toxicity: No classification proposed

Reproductive toxicity:

Specific target organ systemic toxicity (single exposure): Category 1 - Causes damage to organs.(Respiratory system)

Components contributing to classification: 4,4'-Diphenylmethane diisocyanate. Aromatic polyisocyanate.

Specific target organ systemic toxicity (single exposure): Category 3 - May cause respiratory irritation.

Components contributing to classification:

Specific target organ systemic toxicity (repeated exposure): Category 1 - Causes damage to organs through prolonged or repeated exposure.(Respiratory system)

Components contributing to classification: 4,4'-Diphenylmethane diisocyanate. Aromatic polyisocyanate. Diphenylmethane diisocyanate.

Aspiration hazard: No classification proposed

12. ECOLOGICAL INFORMATION

ECOTOXICITY:

Chemical Name	Ecotoxicity
4,4'-Diphenylmethane diisocyanate	<u>Fish:</u> Species > 1,000 mg/196 h <u>Invertebrates:</u> Daphnia magna > 1,000 mg/148 h
Aromatic polyisocyanate	N.D.

Product: FUSOR® 132, 133 PLASTIC REPAIR ADH PT A, Effective Date: 03/10/2023

Diphenylmethane diisocyanate	N.D.
Carbon black	N.D.

PERSISTENCE AND DEGRADABILITY: Not determined for this product.

BIOACCUMULATIVE: Not determined for this product.

MOBILITY IN SOIL: Not determined for this product.

OTHER ADVERSE EFFECTS: Not determined for this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

14. TRANSPORT INFORMATION

This product is NOT REGULATED for non-bulk shipments. For the most accurate shipping information, refer to your transportation/compliance department regarding changes in package size, mode of shipment or other regulatory descriptors.

15. REGULATORY INFORMATION

INTERNATIONAL REGULATIONS: AS FOLLOWS -

AUSTRALIA INVENTORY OF EXISTING CHEMICAL SUBSTANCES (AICS):

All components of this product are on the AICS list.

16. OTHER INFORMATION

Revision: Section 1

Effective Date: 03/10/2023

DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.